



# PENTA

MACHINE CO.

[www.pentamachine.com](http://www.pentamachine.com)

[info@pentamachine.com](mailto:info@pentamachine.com)

1.406.451.3799

 [pentamachineco](https://www.instagram.com/pentamachineco)

## SOLO

## SPECIFICATIONS

### MAX TRAVEL

X: 9.5 in (240 mm)

Y: 6.8 in (172 mm)

Z: 6.2 in (155 mm)

B: -145° to 145°

C: Continuous rotation  
(-99999° to +99999°)

### Max Travel From The Center of Rotation

X: -3 in to 6.5 in (-76 mm to 165 mm)

Y: -3.4 in to 3.4 in (-86 mm to 86 mm)

- ▶ Tested on G5 titanium,  
6061 aluminum, 303  
stainless, machinable  
wax, acetal

Accepts standard

G Code: .ngc, .nc, .txt, .cnc files

Test G Code at

[sim.pentamachine.com](http://sim.pentamachine.com)



| AXIS                                         |  | MAX TRAVEL                                  | SPEED                      |
|----------------------------------------------|--|---------------------------------------------|----------------------------|
| X                                            |  | 9.5 in (240 mm)                             | 590 in/min (15,000 mm/min) |
| Y                                            |  | 6.8 in (172 mm)                             | 590 in/min (15,000 mm/min) |
| Z                                            |  | 6.2 in (155 mm)                             | 590 in/min (15,000 mm/min) |
| B                                            |  | -145° to 145°                               | 88°/second                 |
| C                                            |  | Continuous rotation<br>(-99999° to +99999°) | 88°/second                 |
| Closed Loop Servo Motors                     |  |                                             |                            |
| 12mm diameter<br>C5 preloaded<br>ball screws |  | 51:1 zero backlash<br>strain wave gearing   |                            |
| Linear Bearings                              |  | 15mm double row preloaded                   |                            |

| AXIS |  | RESOLUTION                |
|------|--|---------------------------|
| X    |  | 0.00003 in (0.78 microns) |
| Y    |  | 0.00003 in (0.78 microns) |
| Z    |  | 0.00003 in (0.78 microns) |
| B    |  | 0.001°                    |
| C    |  | 0.001°                    |

| SPINDLE                             |              |
|-------------------------------------|--------------|
| Spindle Speed                       | 18,000 RPM   |
| Power Output                        | 1.3 kW       |
| Spindle Motor                       | Asynchronous |
| Spindle Runout                      | ~1 micron    |
| Tool Change                         | HSK - E - 25 |
| Maximum Tool Length 4.5 in (116 mm) |              |

| MACHINE CONTROL                  |                                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Kinetic Control                  |                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Accepts standard RS274NGC G code |                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Features                         | <ul style="list-style-type: none"> <li>• Active Thermal Stabilization System</li> <li>• Flood Coolant</li> <li>• Tool Center Point Control (TCPC)</li> <li>• Rotated Work Offsets (RWO)</li> <li>• 14 Tool Automatic Tool Changer with tool setter</li> <li>• Probe with wireless charging</li> <li>• Table clamp / Unclass / Turbo</li> <li>• Table taper air purge</li> <li>• Aux - Through Table Air - 2 ports</li> </ul> |
| Connectivity                     | Ethernet, USB                                                                                                                                                                                                                                                                                                                                                                                                                |
| Power Consumption                | 1,800 Watts at 110v Or 220v                                                                                                                                                                                                                                                                                                                                                                                                  |

| COMPONENTS                                                                                                                                                                                                                                                                |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 6061 Aluminum Frame                                                                                                                                                                                                                                                       |
| Polymer Concrete Base                                                                                                                                                                                                                                                     |
| Machine Weight ~1500 lb (680 kg)                                                                                                                                                                                                                                          |
| Cutting Fluid Capacity 7 gallons (26 liters)                                                                                                                                                                                                                              |
| Chip Bin Capacity 7 gallons (26 liters)                                                                                                                                                                                                                                   |
| Machine Footprint<br>For transport only: 23 inches wide x 39.7 inches deep x 66.4 inches tall (58.5cm x 100.9cm x 168.7cm)<br>Recommended for use: 72.5 inches wide X 72.2 inches deep X 85.3 inches tall (185 cm x 184 cm x 217 cm)<br><i>Fits through standard door</i> |



**PENTA**  
MACHINE CO.